

# KT-DPF | Multi-range cable grommets, grey

in pyramid shape, for cable diameters 3-26 mm / IP54 / UL Type 12



The KT-DPF grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. Due to the flexibility and unique pyramid shape, routing and flexible positioning of rigid cables is much easier compared to using conventional cable glands.

The KT-DPF grommets are not split and therefore only usable for cables without connectors.

It is recommended that additional strain relief be provided for the cables using a cable tie.

**Cutting of KT-DPF grommets:** Cable diameter less 20%.



## Specifications


<b>IP rating (EN 60529)</b>	IP54
<b>UL Type (UL 50E)</b>	UL Type 12
<b>Material</b>	Elastomer
<b>Flame class</b>	UL94-V0, self-extinguishing
<b>Operating temperature</b>	-40 C° to 100 C°
<b>Properties</b>	silicone free, halogen free

## Advantages & Benefits

- Large clamping range of 3 to 26 mm with only 3 grommets
- Ideal for wiring non pre-terminated cables locally
- Easy storage

## Product Types & Sizes


### KT-DPF-A gy



Part No.	<b>41260</b>
EAN	<b>4251269306730</b>
Package quantity	<b>10</b>
For max. no. of cables	<b>1</b>
Color	<b>gray (similar RAL 7035)</b>
Length	<b>21 mm</b>
Width	<b>21 mm</b>


Height	<b>50 mm</b>
Mounting height	<b>33 mm</b>
For cable type	<b>Round cable</b>
attr.Klemmbereich kombiniert	<b>3 - 12 mm</b>
Clamping range	<b>1 x 3 - 12 mm</b>

### KT-DPF-B gy



Part No.	<b>41261</b>
EAN	<b>4251269306747</b>
Package quantity	<b>10</b>
For max. no. of cables	<b>1</b>
Color	<b>gray (similar RAL 7035)</b>
Length	<b>41,5 mm</b>
Width	<b>42 mm</b>

Height	<b>59 mm</b>
Mounting height	<b>42 mm</b>
For cable type	<b>Round cable</b>
attr.Klemmbereich kombiniert	<b>4 - 18 mm</b>
Clamping range	<b>1 x 4 - 18 mm</b>



Part No.	<b>41262</b>	Height	<b>59 mm</b>
EAN	<b>4251269306754</b>	Mounting height	<b>42 mm</b>
Package quantity	<b>10</b>	For cable type	<b>Round cable</b>
For max. no. of cables	<b>1</b>	attr.Klemmbereich kombiniert	<b>14 - 26 mm</b>
Color	<b>gray (similar RAL 7035)</b>	Clamping range	<b>1 x 14 - 26 mm</b>
Length	<b>41,5 mm</b>		
Width	<b>42 mm</b>		